



ESI Unitary System Refrigerant Charge

1. How to enter AUTO charge mode-----	2
2. Charging by refrigerant coefficient-----	3
3. Charging by weigh-in method-----	4
TIPS: How to adjust indoor TXV opening-----	5




1. How to enter AUTO charge mode?

Turn on the system, **set 5° F lower than indoor temperature in cooling mode** at thermostat to complete this AUTO charge mode.


Charging method	Outdoor Ambient Temperature	System operation mode when charging
Auto charge mode by refrigerant coefficient	50° F < T < 115° F	Cooling only
Sub-cooling		
Weigh-in	-3° F < T < 122° F	-

Press and hold BS4 for five (5) seconds until **SEG1 displays blinking 7**, then wait one minute to enter AUTO charge mode.

NOTE: Start-up control is enforced to complete prior to activate this AUTO charge mode. It may take 4 to 10 minutes to exit start-up control procedure and fix the compressor speed (RPS) as the following table.



EODA18H-2436




EODA18H-4860


SEG1

SEG2

SEG3



1 minute



Capacity ^{*1}	Compressor speed (RPS)	
	AUTO charge mode OR Pump Down ^{*2} in cooling	Pump Down ^{*2} in heating
2Ton	56	66
3Ton	66	80
4Ton	56	58
5Ton	66	70

Remarks:

1. Select the required capacity by dip the 2nd switch of SW1 on main control board (MCB).
2. Show low pressure on 7 segment display (LED).

2. Charging by refrigerant coefficient

Apply charging and refrigerant adjustment in **cooling mode**.

If outdoor ambient temperature is below 50°F, use weigh-in charge method only.



Refrigerant coefficient is used to evaluate the refrigerant level in the ecoer systems.



- I. Run the system for 15 to 20 minutes and check the coefficient number (here short for “X”, $0 < X < 1$) from the LED display. A perfect charging should be displayed 0.5. **But if the LED displays “--” for more than 20 minutes, stop charging and adjust the TXV opening to ensure required compressor suction superheat (SSH).**
- II. If $X > 0.6$, **remove refrigerant**; or $X < 0.4$, **add more refrigerant**. Then wait for 5 minutes to allow system pressure balanced. Check the new coefficient number to make sure you get 0.5. (0.4 to 0.6 is acceptable if $7^{\circ}\text{F} \leq \text{SSH} \leq 20^{\circ}\text{F}$.)

Note: Maintain a minimum operation of 5 minutes after every refrigerant amount or TXV opening adjustment. Technically, gauges are not required in this charging method.

Ecoer Smart Service Pro App shows live system pressure and temperature data. (In order to make data available on your smart phone, register the system via Ecoer Smart Service Pro App before charging.)

[How to end AUTO charge mode]


- Press **BS4 once**
- Automatically exit in 2 hours
- Turn off the system at thermostat

Model	Designed sub-cooling degree (SC)
2Ton	8°F (±2°F)
3Ton	10°F (±2°F)
4Ton-5Ton	8°F (±2°F)


3. Charging by weigh-in method

Weigh-in method can be used for the initial installation, or anytime a system charge needs to be replaced. Weigh-in method can also be used when power is not available on job site or ambient temperature is improper to use refrigerant coefficient and sub-cooling charge method.

When use weigh-in method in heating mode, make sure the liquid line sub-cooling degree (SC) and compressor discharge superheat (DSH) meet the target value.



Query live data by BS3 button to calculate DSH or check SC and DSH via ESS Pro App.



Use **gauge port** connected to compressor suction side to charge the system in heating mode.

Model	Factory charge	Air Handler	Charge amount for air handler	Charge multiplier for liquid line length ^{*2}
2436	See nameplate	24K	0	0.6 oz/ft
		36K	14oz ^{*1}	
4860		36K	0	
		48K	11oz ^{*3}	
		60K	11oz ^{*3} +14oz ^{*1}	

1.

An additional amount of refrigerant adjustment is required for a large indoor coil. Invalid for system with electric heater or other third-party heat source whose capacity is 1.2 times of heat pump nominal capacity. (e.g. No additional charge for a 3 Ton system equipping with a 15kW indoor electric heat kit.)

15/(3*3.52)=1.42 >1.2

Note: 1Ton=3.52kW
2.

Every condensing unit is factory charged for 25ft of standard size line set. A refrigerant adjustment may be necessary if the line set length is over or under the pre-charged 25 ft (adding or removing 0.6 oz/ft on 3/8 liquid line respectively).
3.

Compensate 11oz charge for units built on and after Dec 1, 2019.

TIPS: How to adjust indoor TXV opening

To keep the best performance and reliability of Ecoer Smart Inverter (ESI) system, be sure liquid line sub-cooling (SC) and compressor suction superheat (SSH) meet our requirements.




Target SC and SH
in cooling



- If the LED displays “--” in AUTO charge mode for more than 20 minutes, stop charging and use a wrench to **clockwise** the TXV to ensure $SSH \geq 7^{\circ}F$.
- In case that the cooling performance is abnormal due to improper superheat (i.e. $SSH > 20^{\circ}F$). Proceed as follows to complete the field adjustment.
 1. Activate AUTO charge mode from outdoor condensing unit to fix compressor speed (RPS) by press BS4 for 5 seconds on MCB. Run the system for 15 to 20 minutes and check refrigerant coefficient number from LED display or ESS Pro App, **add refrigerant until you get 0.6**.
 2. Open the front panel of the indoor unit, then use a wrench to **counterclockwise** the TXV **until $SSH \leq 20^{\circ}F$** . This will make more refrigerant flow into indoor coil for better cooling performance.

NOTE: Maintain a minimum operation of 5 minutes after every refrigerant amount or TXV opening adjustment, then check live SC and SSH on ESS Pro App.



Remember:
Put back the panel after TXV adjusted.

©2022 ECOER INC.

43671 Trade Center Place, Suite 100
Dulles, VA 20166

Tel: 703-348-2538

www.ecoer.com